









The Deluxe collection is inspired by nature and offers rare stones in an exquisite color pallet. Nine various full body products are provided in multiple sizes, two textures, beautiful mosaics and trim pieces are also available.

# **Deluxe** Collection



Polished

Polished



24 x 24 IRH2424014 IRP2424014



IRP1224014

Perla







IRH1224008 IRP1224008

Crema



Delorian Grey

in color and/or texture.

24 x 24 IRH2424011



IRP2424011

\* When preparing the order, the surfaces are selected randomly, therefore, the continuity of textures is not guaranteed. \* Color samples are for a general reference only. Tile is made with all natural materials; therefore, is subject to variation









# Colors / Sizes / Finishes

12 x 24 IRH1224018 IRP1224018







Ocean Storm



IRP1224012







Absolute Black



**Deluxe** Mosaics



## Diamond Mosaic

1 x 1 mesh mounted on 12 x 12 sheet

	Honed	Polished
rla	IRH12MD114	IRP12MD114
ema	IRH12MD108	IRP12MD108
lorian Grey	IRH12MD111	IRP12MD111
ean Storm	IRH12MD118	IRP12MD118
solute Black	IRH12MD112	IRP12MD112



# Classic 01 Mosaic

3 x 3 mesh mounted on 12 x 12 sheet

Honed	Polished
IRH12MC114	IRP12MC114
IRH12MC108	IRP12MC108
IRH12MC111	IRP12MC111
IRH12MC118	IRP12MC118
IRH12MC112	IRP12MC112



## Herringbone 01 Mosaic

1 x 2 mesh mounted on 12 x 12 sheet

i x z illesii illooliled	OII 12 X 12 SHEEL
Honed	Polished
IRH12MH114	IRP12MH114
IRH12MH108	IRP12MH108
IRH12MH111	IRP12MH111
N/A	N/A
IRH12MH112	IRP12MH112



#### Lines 01 Mosaic

1 x 12 mesh mounted on 12 x 12 sheet

Honed	Polished
IRH12ML114	IRP12ML114
IRH12ML108	IRP12ML108
IRH12ML111	IRP12ML111
IRH12ML118	IRP12ML118
IRH12ML112	IRP12ML112



#### Brick 01 Mosaic

1 x 2 mesh mounted on 12 x 12 sheet

Honed	Polished
IRH12MB114	IRP12MB114
IRH12MB108	IRP12MB108
IRH12MB111	IRP12MB111
IRH12MB118	IRP12MB118
IRH12MB112	IRP12MB112



## Brick 02 Mosaic


3 x 6 mesh mounted on 12 x 12 sheet

Honed	Polished
IRH12MB214	IRP12MB214
IRH12MB208	IRP12MB208
IRH12MB211	IRP12MB211
IRH12MB218	IRP12MB218
IRH12MB212	IRP12MB212

Crema

Delorian Grey

Ocean Storm







**Deluxe** Trim **Deluxe** Trim



#### Bullnose 3 x 12

	Honed	Polished
erla	IRH312B014	IRP312B014
rema	IRH312B008	IRP312B008
elorian Grey	IRH312B011	IRP312B011
Ocean Storm	IRH312B018	IRP312B018
bsolute Black	IRH312B012	IRP312B012



# Double Bullnose Right

		_	
3	x 12		
Honed		Polished	
IRH312B314		IRP312B31	4
IRH312B308		IRP312B30	8(
IRH312B311		IRP312B31	1
IRH312B318		IRP312B31	8
IRH312B312		IRP312B31	2



# Double Bullnose Left

3 >	x 12
Honed	Polished
IRH312B614	IRP312B614
IRH312B608	IRP312B608
IRH312B611	IRP312B611
IRH312B618	IRP312B618
IRH312B612	IRP312B612



## Cove Base

6 x 12 IRH612C014 IRH612C008 IRH612C011 IRH612C018 IRH612C012



# In Corner

IRH16IC014 IRH16IC008 IRH16IC011 IRH16IC018 IRH16IC012



# **Out Corner**

1 x 6 IRH16OC014 IRH16OC008 IRH16OC011

IRH16OC018

IRH16OC012



Stair Tread 12 x 12

IRH12ST014 Crema Delorian Grey Ocean Storm IRH12ST012 Absolute Black


















 $\begin{array}{ccc} \text{C1028} & & \text{Acutest} \\ \text{COF} & & \text{DCOF} \\ \text{Dry} & \geq 0.80 & \text{Wet} & \geq 0.42 \\ \text{Wet} & \geq 0.70 & & \end{array}$ 

# **Deluxe** Tech Specs

PHYSICAL PROPERTIES	TEST	INDUSTRY STA	INDUSTRY STANDARDS			
Water Absorbtion Size	ASTM C373	0.5% Maximum		≤ 0.1%		
Calibrated (non rectified)	ASTM C499	• Range of Thickness (inch)	0.040	≤ 0.040		
	ASTM C499	Average Facial Dimension	± 0.50%	≤ ± 0.50%		
	ASTM C485	• Warpage	±75% on any edge	≤ ± 0.75%		
	ASTM C485	• Warpage	$\pm$ 50% on diagonal	≤ ± 0.50%		
	ASTM C502	• Wedging	± 0.50%	≤ ± 0.50%		
Rectified	ASTM C499	• Range of Thickness (inch)	0.040	≤ 0.040		
	ASTM C499	Average Facial Dimension	± 0.25%	≤ 0.25%		
	ASTM C485	• Warpage	± 0.40% on any edge	≤ 0.40%		
	ASTM C485	• Warpage	$\pm$ 0.40% on diagonal	≤ 0.40%		
	ASTM C502	• Wedging	± 0.25%	≤ 0.25%		
Bond Strength	ASTM C482	50 psi or greater		> 200 psi		
Deep Abrasion	ASTM C1243	< 175 mm <sup>3</sup>		< 150 mm <sup>3</sup>		
Hardness (Mohs scale)		No requirement		≥7		
Frost Resistance (Freeze/Thaw)	ASTM C1026	No sample must show		No cracking		
		alterations to surface		or spalling occurred		
Chemical Resistance	ASTM C650	No requirement		Class A		
Breaking Strength	ASTM C648	250 lbf or greater		≥ 500 lbf		
Coefficient of Friction (static)	ASTM C1028	No requirement		Per collection		

Data taken from a representative through body collection. Individual product testing can be conducted by request.

Coefficient of Friction: all values are given for matte or honed material. No values are given for polished material. Iris U.S. does not recommend polished surfaces in areas subject to exposure from grease, oil or water. (All values are based on ASTM C1028 and Acutest DCOF). The above information is a subject to change.

# **Deluxe** Packaging

PRODUCT	FINISH		SIZE	BOX/F	PCS	BOX SF	PALLET/	BOXES	PALLET/SF	THICKNE	SS \	WEIGHT LB/SF
Floor & Wall Tile	Honed / Polishe	ed	24" x 24"	4		15.834	3	0	475.02	9 mm		4.55
	Honed / Polishe	ed	12" x 24"	8		15.751	3:	2	504.032	9 mm		4.55
Mosaics 12"x12" Sheet	FINISH	SIZE	BOX/PCS	BOX/SF	LB/PIECE		Trims	FINISH	SIZE	BOX/PCS	BOX/SF	LB/PIECE
Brick 01	Honed / Polished	1"x 2"	5	4.896	4.55		Bullnose	Honed/Polished	3"x 12"	33	7.994	0.95
Brick 02	Honed / Polished	3"x 6"	5	4.896	4.55		Cove Base	Honed	6"x 12"	8	3.88	1.70
Classic 01	Honed / Polished	3"x 3"	5	4.896	4.55		In Corner	Honed	1"x 6"	4	0.16	0.15
Diamond 01	Honed / Polished	1"x 1"	5	4.896	4.55		Out Corner	Honed	1"x 6"	4	0.16	0.15
Herringbone 01	Honed / Polished	1"x 2"	5	4.896	4.55		Stair Tread	Honed	12"x 12"	10	9.793	4.55
Lines 01	Honed / Polished	1"x 12"	5	4.896	4.55							